


Product data sheet

SIRIUS 600 - CC GROUND RECESS
9066-K-2-688-01
UNILAMP




Description SIRIUS a brand new linear light family features various mounting application types including in-ground walk over, wall mounted, ceiling mounted, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	4.3 W	LOR	100%
Lamp flux	179 lm	ULOR	100%
Luminous efficacy	42 lm/W	Total flux	179 lm
CCT	4000 K	Total power	4.3 W
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	4.5 W	LOR	100%
Lamp flux	125 lm	ULOR	100%
Luminous efficacy	28 lm/W	Total flux	124 lm
CCT	0 K	Total power	4.5 W
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	4.1 W	LOR	100%
Lamp flux	369 lm	ULOR	100%
Luminous efficacy	90 lm/W	Total flux	368 lm
CCT	8000 K	Total power	4.1 W
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	3.4 W	LOR	100%
Lamp flux	179 lm	ULOR	100%
Luminous efficacy	53 lm/W	Total flux	179 lm
CCT	0 K	Total power	3.4 W
CRI	-36		

Mounting mode

Floor recessed

Shape and measurements

Length: 24.09 in

Width: 3.70 in

Height: 5.41 in

Adjustability

Fixed

Electric

System power: 16.3 W

Appliance Class: III

Protection

IP: 67

IK: 10