

# Product data sheet


GUSTAV II (1-ARMED)  
9.682.2036.07  
LEIPZIGER LEUCHTEN



IP  
55


Mounting height of 4.00 to 5.00 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure sodium vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W    | LOR         | 54%     |
| Lamp flux          | 3500 lm | ULOR        | 11%     |
| Luminous efficacy  | 30 lm/W | Total flux  | 1878 lm |
| CCT                | 2000 K  | Total power | 62 W    |
| CRI                | 25      |             |         |



### 1 x High pressure sodium vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W    | LOR         | 54%     |
| Lamp flux          | 5600 lm | ULOR        | 11%     |
| Luminous efficacy  | 36 lm/W | Total flux  | 3004 lm |
| CCT                | 2000 K  | Total power | 83 W    |
| CRI                | 25      |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 29.13 in  
Diameter: 9.84 in

## Electric

System power: 62-83 W

## Protection

IP: 55