

Product data sheet

FLAT POLYMERO KREIS
311611.002.4
RZB




IP
40

IK
10

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, H 93 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 2100lm System power: 29W Beam Angle: 119° Number of fittings B10A: 5 Number of fittings B16A: 13 Number of fittings C10A: 14 Number of fittings C16A: 22 Inrush current: 20A Unified Glare Ratio: 18,5 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 29 W | CRI | 80 |
| Total flux | 2100 lm | LOR | 100% |
| Luminous efficacy | 72 lm/W | ULOR | 10% |
| | | Total power | 29 W |

Mounting mode

Ceiling mounted

Electric

System power: 29 W

Shape and measurements

Height: 3.66 in
Diameter: 18.11 in

Protection

IP: 40
IK: 10

Adjustability

Fixed