

# Product data sheet

LENSES-EE0597DAWS830B0175  
0837710  
RIDI




IP  
20

Recessed LED luminaire Design: Recessed LED single luminaire for 600 or 625 modular ceilings. Rigid luminaire housing in white steel (similar to RAL 9016) with square 4-row lens arrays for high-efficiency light yield. Diffuser held in the luminaire housing with spring catches, hinges down on both sides. LED modules formed as a flat board. Mid-power LEDs for even illumination and maximum efficiency. LED driver prefitted in luminaire housing. Colour rendering in index Ra  $\geq$  80, colour temperature 3000 Kelvin (830). Electronic DALI converter for LED, 220-240 Volt, 0/50-60 Hz and internal connector block. Suitable for direct voltage operation and use in central battery systems, 220-240 VDC.

Mounting: Installation in various ceiling systems using suitable fixing kits or lay-in mounting in exposed trunking ceiling systems with lay-in ceiling tiles. No additional fixing accessories are required for this.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	1710 lm	LOR	100%
Luminous efficacy	171 lm/W	Total power	10 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.50 in  
Width: 11.69 in  
Height: 2.32 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 10 W

## Protection

IP: 20