

Product data sheet


LSRS8B/LSRSWM8B LED 8" SHALLOW ROUND CYLINDERS
LSR8B60D010 EC8B60930 8LBN0WMH
COOPER LIGHTING



IP
47

Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-6,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	59.5 W	CRI	100
Total flux	4527 lm	LOR	100%
Luminous efficacy	76 lm/W	Total power	59.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in
Width: 3.94 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 59.5 W

Protection

IP: 47