


Product data sheet

ARIZONA 5 POST TOP LUMINAIRES
AR-21052-T2-W40
LIGMAN



· Lamp LED · CRI Ra > 80 · MacAdam Ellipse 3 SDCM · Colour 3000K and 4000K · Life time L90B10 Ta 25° C 135,000, 300,000 · Life time L80B10 Ta 50° C 310,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector or PMMA lens - Clear, acrylic PMMA diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	35.1 W	CRI	80
Total flux	3562 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	35.1 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 150.98 in
Diameter: 8.86 in
Weight: 20 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 35.1 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C