


Product data sheet

SMART CAKE 160 IP55 LED GE 2700K FLOOD BLACK STRUC
13004632
MODULAR




Soft light Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


Light output 1




1 x LED			
Nominal lamp power	36.3 W	LOR	79%
Lamp flux	3949 lm	Total flux	3110 lm
Luminous efficacy	86 lm/W	Total power	36.3 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	49.7 W	LOR	79%
Lamp flux	5107 lm	Total flux	4021 lm
Luminous efficacy	81 lm/W	Total power	49.7 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	16 W	LOR	79%
Lamp flux	2020 lm	Total flux	1591 lm
Luminous efficacy	99 lm/W	Total power	16 W
CCT	2700 K		
CRI	90		




1 x LED

Nominal lamp power	23.5 W	LOR	79%
Lamp flux	2751 lm	Total flux	2166 lm
Luminous efficacy	92 lm/W	Total power	23.5 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	30.8 W	LOR	79%
Lamp flux	3415 lm	Total flux	2689 lm
Luminous efficacy	87 lm/W	Total power	30.8 W
CCT	2700 K		
CRI	90		



1 x LED

Nominal lamp power	42 W	LOR	79%
Lamp flux	4436 lm	Total flux	3493 lm
Luminous efficacy	83 lm/W	Total power	42 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in

Width: 6.30 in

Height: 4.76 in

Weight: 0.98 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W

Appliance Class: II

Protection

IP: 55