


Product data sheet

UTAH 1 FLOODLIGHTS, PROJECTORS
UT-50572-M-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single entry - One cable gland supplied with 0.5 m of 2x0.5 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Include control gear for UT-50571, UT-50572 - Remote driver is not included for UT-50552, UT-50553, UT-50555, UT-50562, UT-50563, UT-50565 - Plastic ground spike for garden type

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	7.3 W	CRI	80
Total flux	315 lm	LOR	100%
Luminous efficacy	43 lm/W	Total power	7.3 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 2.99 in
Diameter: 1.77 in
Weight: 0.28 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 7.3 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C