# Product data sheet

MINI MULTIPLE FOR SMART KUP LED 4000K SPOT GE ALU-BLACK 12524205+12556202

MODULAR






1 v I ED




Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your chouce. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with Smart by adding the Smart frontrings to your recessed spot.

#### Light output 1



IXLED	
Nominal lamp power	6.2 W
Lamp flux	590 lm
Luminous efficacy	82 lm/W
CCT	4000 K
CRI	90

LOR	87%
Total flux	511 lm
Total power	6.2 W



I X LED			
Nominal lamp power	9.2 W	LOR	
Lamp flux	792 lm	Total flux	
Luminous efficacy	75 lm/W	Total power	
CCT	4000 K		
CRI	90		

#### Mounting mode

Ceiling recessed, Wall recessed

### Shape and measurements

Length: 4.72 in Width: 4.72 in Height: 4.72 in Weight: 0.69 kg

# Adjustability

Free

### Electric

System power: 6.2-9.2 W Appliance Class: III

## Protection

IP: 20 IK: 01 87% 686 lm 9.2 W