


# Product data sheet

LTP434 IP44:LED-FT-37W/3K  
116-0210  
WE-EF



IP44, Class I. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gaskets. Prismatic polycarbonate lenses, 3 x 120° offset. Anodised aluminium reflector. Factory installed LED circuit board. LED boards can be easily removed for upgrading. Service door with fused cable connecting box. Trilight Column Three sided light output HIT 35 W IP44. Marine-grade all aluminium construction. 5CE superior corrosion protection including PCS hardware. Powdercoat finish in black RAL 9004, grey aluminium RAL 9007 or white RAL 9016. Silicone rubber gaskets. Prismatic polycarbonate lenses. Service door with fused cable connecting box. Integral electrical control gear.

## Light output 1



1 x LED			
Nominal lamp power	37 W	LOR	40%
Lamp flux	6380 lm	ULOR	5%
Luminous efficacy	61 lm/W	Total flux	2547 lm
CCT	3000 K	Total power	42 W
CRI	80		

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 59.06 in  
Diameter: 8.07 in  
Weight: 16.6 kg

## Design

Color of housing: Black, Silver gray, White

## Electric

System power: 42 W  
Appliance Class: I

## Protection

IP: 44