Product data sheet

FLAT MOON 650 SUSPENSION UP-DOWN LED 3000K GI WHITE STRUC 13305009

MODULAR






IP 20

Enchanting moonlight Contemporary architectural projects love a minimalist, slim lighting design. Flat moon is a stylish, reduced height fixture (78 mm) that distributes a soft, yet functional light. Office-compliant when combined with one of the prismatic diffusers, it is also a perfect fit for public spaces, hotels, restaurants or retail environments. Exceptionally versatile, Flat moon can be either surface-mounted, recessed or suspended (with two types of suspension kits for either down or up/down lighter) and even directly mounted and connected onto the gear. It comes in three sizes: 450, 650 or 950 mm diameter.

Light output 1



| I X LED |
|--------------------|
| Nominal lamp power |
| Lamp flux |
| Luminous efficacy |
| CCT |
| CRI |
| |

| 85 W |
|----------|
| 10120 lm |
| 82 lm/W |
| 3000 K |
| 90 |
| |

| LOR | 80% |
|-------------|---------|
| ULOR | 23% |
| Total flux | 8060 lm |
| Total power | 98 W |
| | |

Mounting mode

Pendant

Shape and measurements

Length: 25.59 in Width: 25.59 in Height: 3.07 in Weight: 10.5 kg

Adjustability

Fixed

Electric

System power: 98 W

Protection

IP: 20