


# Product data sheet

FLAT POLYMERO  
312092.002.2  
RZB




IP  
40

IK  
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 150 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3250lm System power: 33W Beam Angle: 120° Number of fittings B10A: 53 Number of fittings B16A: 85 Number of fittings C10A: 53 Number of fittings C16A: 85 Inrush current: 0,2A Unified Glare Ratio: 20,1 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	33 W	CRI	80
Total flux	3250 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	12%
		Total power	33 W

## Mounting mode

Wall mounted

## Electric

System power: 33 W

## Shape and measurements

Height: 5.91 in  
Diameter: 20.28 in

## Protection

IP: 40  
IK: 10

## Adjustability

Fixed