


Product data sheet

PURE 3 SPOT TRACK
09.1915 CDMR-111/35W/10°24°40°
FLOS




Luminaire for three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.


Light output 1



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx8.5
Lamp flux	3200 lm	LOR	51%
Luminous efficacy	42 lm/W	Total flux	1619 lm
CCT	3000 K	Total power	39 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx8.5
Lamp flux	3200 lm	LOR	51%
Luminous efficacy	42 lm/W	Total flux	1630 lm
CCT	3000 K	Total power	39 W
CRI	80		



1 x Metal halide lamp			
Nominal lamp power	35 W	Socket	Gx8.5
Lamp flux	3200 lm	LOR	42%
Luminous efficacy	34 lm/W	Total flux	1343 lm
CCT	3000 K	Total power	39 W
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 39 W
Appliance Class: I

Shape and measurements

Length: 1.69 in

Width: 5.63 in

Height: 6.22 in

Adjustability

Free

Protection

IP: 20