

# Product data sheet


RAY F1 DIFF.VETRO.GRI.  
F5915020  
FLOS



IP  
20

Floor lamp providing diffused lighting. Steel tube (10 mm diam.) structure, welded, brushed and chrome-plated. Diffuser support disk in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. Resistive dimmer wired on cord for 0-100% light adjustment. Power cord with black PVC/PVC (flat) sheath (1500 mm). Net weight glass diffuser 8 kg metal diffuser 5 kg.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	150 W	Socket	E27
Lamp flux	2500 lm	LOR	52%
Luminous efficacy	9 lm/W	ULOR	25%
CCT	2821 K	Total flux	1303 lm
CRI	99	Total power	150 W

## Mounting mode

Standing / Bollard, Floor mounted

## Shape and measurements

Length: 16.52 in  
Width: 16.52 in  
Height: 50.58 in

## Adjustability

Fixed

## Electric

System power: 150 W

## Protection

IP: 20