


# Product data sheet

EBRME6-R2X145/35ND-SM-350M840  
0850065  
RIDI



Recessed LED luminaire EBRME6-R Design: Stand alone luminaire for 600x600 ceilings. White coated steel, with low profile. For R-TUBE lamps (must be ordered separately). Electronic converter for LED, 230 Volt, 0/50-60 Hz and internal connector block. Suitable for direct voltage operation and use in central battery systems. Mounting: Simple lay-in installation in ceilings with exposed T-bars and installation in sawn ceiling openings using suitable fixing kits. EBRME6-R ... SM Parabolic mirror louvre SM in high-reflectance, matt anodised super-purity aluminium with silver coating.

## Light output 1



2 x LED			
Nominal lamp power	26 W	LOR	85%
Lamp flux	3640 lm	Total flux	6205 lm
Luminous efficacy	119 lm/W	Total power	52 W
CCT	4000 K		
CRI	80		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 58.94 in  
Width: 11.69 in  
Height: 2.36 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 52 W

## Protection

IP: 20

## Other operating numbers

Ambient temperature range: -40...122°F