


Product data sheet

LOUI 50
925340.003
RZB




IP
20

IK
03

Series: LESS IS MORE 50 system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Colour: jet black (RAL 9005) Length L: 1961 mm Width B: 71 mm Height H: 1.5 mm Cut-out length LA: 1968 mm Cut-out width BA: 60 mm Recess height HE: 100 mm Luminaire: recess height HEL: 75 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI):80 System power 1: 47 W Rated luminous flux 1: 5400 lm Luminous efficiency: 115 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	47 W	CRI	80
Total flux	5400 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	47 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 2.24 in
Width: 77.17 in
Height: 0.08 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 47 W

Protection

IP: 20
IK: 03