


Product data sheet

WALL MOUNTED LUMINAIRE TOLEDO 660 - WITH EXTERNAL LOUVERS 4000K
10.01223.0VXXX + 10.41210.0V001
HESS




Domed luminaire canopy, horizontally separated in two, made of aluminium, underside painted white. Support elements made of aluminium. Cylindrical luminaire enclosure made of PMMA. Round luminaire body made of aluminium, optionally with or without louvres. 10.31201.2V001 PARALLEL ROHRE Bracket TOLEDO 660 double Made of galvanised steel Overhanging 450 mm on each side Spigot pole \varnothing 76,1 mm Colour: DB 703 or all RAL- (classic- single shades), Hess-DB and Hess-Glimmer-colours. RAL pearl-mica-metallic-shades on request.


Light output 1




1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2823 lm	Total flux	2823 lm
Luminous efficacy	101 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2510 lm	Total flux	2510 lm
Luminous efficacy	90 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	2672 lm	Total flux	2672 lm
Luminous efficacy	95 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

28 W
2686 lm
96 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2686 lm
28 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2122 lm
106 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2122 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
1888 lm
94 lm/W
4000 K
80

LOR
Total flux
Total power

100%
1888 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2010 lm
100 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2010 lm
20 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2020 lm
101 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2020 lm
20 W

Mounting mode

Wall mounted

Shape and measurements

Length: 46.13 in

Width: 36.75 in

Height: 37.74 in

Electric

System power: 20-28 W

Protection

IP: 65

Adjustability

Fixed