


# Product data sheet

EPSYLON - POLE TOP LIGHT  
7210-0-3-713-XX  
UNILAMP



EPSYLON is the family of pole top and wall mount luminaires with unshielded symmetrical distribution. The recommended mounting height is between 3 – 5 meters. To avoid discolouration of the lens we have used a high quality PMMA clear cover. The diffuser gives a broad spread light distribution. These luminaires are generally used to illuminate gardens, parks, pedestrian, squares and open spaces. They are assembled with high brightness multiple LEDs. Aluminium pole, galvanized steel pole, pole adaptor and anchorage unit for concrete foundation are also available. • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Spun Aaluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Clear PMMA diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • M20 cable gland or TPE grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	150 W	LOR	56%
Lamp flux	13000 lm	ULOR	8%
Luminous efficacy	87 lm/W	Total flux	7226 lm
CCT	3000 K	Total power	169 W
CRI	84		

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 24.03 in

Width: 24.40 in

Height: 17.64 in

## Adjustability

Fixed

## Electric

System power: 169 W

Appliance Class: I

## Protection

IP: 54

IK: 06