

Product data sheet

ALU-KREIS
25202.002
RZB




IP
43

IK
02

Series: Alu-Kreis Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 280, H 120 Lamp: LED Colour Temperature: 6300K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 580lm System power: 16W Beam Angle: 138° Unified Glare Ratio: 17,6 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 6300 K |
| Nominal lamp power | 16 W | CRI | 60 |
| Total flux | 580 lm | LOR | 100% |
| Luminous efficacy | 36 lm/W | ULOR | 22% |
| | | Total power | 16 W |

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.72 in
Diameter: 11.02 in

Adjustability

Fixed

Electric

System power: 16 W

Protection

IP: 43
IK: 02