



Product data sheet

LOG OUT UP/DOWN WL T16 6X28/54W PMMA
581-03545PM
MOLTO LUCE




Log OUT UP/DOWN T16, Wandleuchte direkt/indirekt strahlend; kantiges, geradliniges Aluminium Strangpressprofil; weiß pulverbeschichtete Oberfläche, Abdeckung aus hochwertigem, flachem „BlendOpal“-Polycarbonat, für direkte Lichtverteilung; Abdeckung für indirekten Anteil ist eine klare PC-Abdeckung für schattenfreie, homogene Lichtverteilung; 3x2x 28/54W T16 G5, 230V, Multiwatt EVG; IP20;

Light output 1



6 x Fluorescent lamp tubular T5

Nominal lamp power	54 W	Socket	G5
Lamp flux	4450 lm	LOR	49%
Luminous efficacy	243 lm/W	ULOR	28%
CCT	3000 K	Total flux	13095 lm
CRI	85	Total power	54 W



6 x Fluorescent lamp tubular T5

Nominal lamp power	28 W	Socket	G5
Lamp flux	2600 lm	LOR	49%
Luminous efficacy	142 lm/W	ULOR	28%
CCT	3000 K	Total flux	7651 lm
CRI	85	Total power	54 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 129.57 in
Width: 2.36 in
Height: 5.71 in

Adjustability

Fixed

Electric

System power: 54 W
Appliance Class: I

Protection

IP: 20