



Product data sheet

EPSILON LED
508001
FLOS



• Wall light for outdoor installation on wall. • Configuration: turned aluminium body (EN AW 6060 alloy). 316L stainless steel fixing bracket. • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Methacrylate diffuser with silkscreen finishing, fixed to the body by a double-sided tape.

Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 2.4 W | LOR | 92% |
| Lamp flux | 144 lm | Total flux | 132 lm |
| Luminous efficacy | 39 lm/W | Total power | 3.4 W |
| CCT | 6000 K | | |
| CRI | 70 | | |

Mounting mode

Wall mounted

Shape and measurements

Length: 2.17 in

Width: 1.38 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 3.4 W

Appliance Class: III

Protection

IP: 65

IK: 05