Product data sheet

WINK 115 LED GE 3000K SPOT BLACK STRUC 13070132


MODULAR







The new Modular recessed spot Not only Wink's technical ingenuity may best be called remarkable, but also its sense of humor. As its name recalls, Wink is a recessed spotlight that likes to wink at you. The straightforward approach, in combination with refined lines and detailed workmanship, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. Wink is perfect for any residential or hospitality project, thanks to its symmetric or asymmetric lighting experience. Its identical design allows you to combine both versions, in order to create different lighting effects in the same room.

Light output 1







Mounting mode

Ceiling recessed

1 x LED			
Nominal lamp power	23.4 W	LOR	80%
Lamp flux	1887 lm	Total flux	1501 lm
Luminous efficacy	56 lm/W	Total power	26.7 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	11 W	LOR	80%
Lamp flux	1034 lm	Total flux	823 lm
Luminous efficacy	58 lm/W	Total power	14.2 W
CCT	3000 K		
CRI	90		
1 x LED			
Nominal lamp power	16.2 W	LOR	80%
Lamp flux	1418 lm	Total flux	1128 lm
Luminous efficacy	58 lm/W	Total power	19.5 W
CCT	3000 K		
CRI	90		

Shape and measurements

Length: 4.53 in Width: 4.53 in Height: 3.94 in Weight: 0.87 kg

Adjustability

Fixed

Electric

System power: 14.2-26.7 W Appliance Class: III

Protection

IP: 54