

Product data sheet

JET 58 CYLINDRICAL BOLLARDS


JE-10581-T3-W40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11.7 W	CRI	80
Total flux	678 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	11.7 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	11.7 W	CRI	80
Total flux	678 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	11.7 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 39.37 in

Diameter: 10.63 in

Weight: 7 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 23.4 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 08

Surface temperature: 40°C