

# Product data sheet


EVA II (W. SHIELD ON SIDE FACING BUILDING)  
9.898.2052.25  
LEIPZIGER LEUCHTEN



IP  
55

For high light requirements, mounting height 4.00 - 5.00 m. - Impact-resistant clear polycarbonate attachment, UV-stabilized - Large aluminium reflector for max. light output, inside in special white paint - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Unit carrier made of hot die cast aluminium, corrosion-resistant, outside painted in colour - All electrical components are arranged on a block - Adapter jack for connection -Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure sodium vapour lamp

|                    |          |             |         |
|--------------------|----------|-------------|---------|
| Nominal lamp power | 100 W    | LOR         | 48%     |
| Lamp flux          | 10400 lm | ULOR        | 10%     |
| Luminous efficacy  | 44 lm/W  | Total flux  | 5005 lm |
| CCT                | 2000 K   | Total power | 115 W   |
| CRI                | 25       |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 17.72 in  
Diameter: 15.75 in

## Electric

System power: 115 W

## Protection

IP: 55