

Product data sheet

SYNDY OVAL POST TOP LUMINAIRES


SY-20644-W40

LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Aluminium parabolic reflector on the top of luminaire - Integral control gear installed under spigot pole - Maximum wind load resistance is 120 km/h

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	55.2 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	57 lm/W	ULOR	3%
		Total power	55.2 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 22.99 in
Diameter: 37.40 in
Weight: 23.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 55.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C