


Product data sheet

RICHARD II (WALL FITTING)
9.844.3162.00
LEIPZIGER LEUCHTEN




Mounting height approx. 3,00 - 4,50 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Circular shield for glare limitation made of anodized aluminium - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 125 W | LOR | 43% |
| Lamp flux | 6800 lm | ULOR | 8% |
| Luminous efficacy | 21 lm/W | Total flux | 2922 lm |
| CCT | 3400 K | Total power | 137 W |
| CRI | 54 | | |



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W | LOR | 43% |
| Lamp flux | 4000 lm | ULOR | 8% |
| Luminous efficacy | 19 lm/W | Total flux | 1719 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |

Mounting mode

Wall mounted, Ceiling mounted

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in

Design

Material impression: Matt

Electric

System power: 89-137 W
Ballast: ECG
Suitable for feed-through wiring

Protection

IP: 55
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...95°F