

Product data sheet

FLAT POLYMERO
311593.002.3.76
RZB




IP
40

IK
10

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (polycarbonate), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 150 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 3700lm System power: 35W Beam Angle: 115° Number of fittings B10A: 10 Number of fittings B16A: 17 Number of fittings C10A: 16 Number of fittings C16A: 26 Inrush current: 49A Unified Glare Ratio: 20,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	3700 lm	LOR	100%
Luminous efficacy	106 lm/W	ULOR	8%
		Total power	35 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.91 in
Diameter: 20.28 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 40
IK: 10