Product data sheet

LUCAS X (1-ARMED BEADED) 9.850.3042.16

LEIPZIGER LEUCHTEN








Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury vapour lamp | | | |
|---------------------------------------|---------|-------------|--|
| Nominal lamp power | 80 W | LOR | |
| Lamp flux | 4000 lm | ULOR | |
| Luminous efficacy | 37 lm/W | Total flux | |
| CCT | 3400 K | Total power | |
| CRI | 54 | | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in Diameter: 22.44 in Electric

System power: 89 W

Protection

IP: 55

83% 2% 3316 lm 89 W