


# Product data sheet

VIGILANT LED LOW BAY 13250 LUMENS, ULTRA WIDE DISTRIBUTION, POLYCARBONATE LENS  
LEX4UN2BXXXXXN  
DIALIGHT



Vigilant LED Low Bay 13,250 Lumens 114 Watts 100-277V AC, 120-250V DC Neutral White, 80CRI Polycarbonate Lens UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE ENEC EN 60598:2015 EN 60598-2-1 (ed.1), IEC 60598-2-1 (ed.8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2010 IEC60068 Salt Spray Testing - Severity 1 IK10 Ultra Wide Distribution IP66/67 Scaled IES File

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3783 K |
| Nominal lamp power | 114 W    | CRI         | 80     |
| Total flux         | 13250 lm | LOR         | 100%   |
| Luminous efficacy  | 116 lm/W | Total power | 114 W  |

## Mounting mode

Pendant

## Shape and measurements

Length: 15.94 in  
Width: 15.94 in  
Height: 8.27 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 114 W  
Appliance Class: I

## Protection

IP: 66  
IK: 10

## Other operating numbers

Ambient temperature range: -40...149°F