

Product data sheet


RICHARD V (W. SHIELD ON SIDE FACING BUILDING)
9.889.3042.20
LEIPZIGER LEUCHTEN



IP
55

Mounting height approx. 4.00 m - 5.00 m, for medium light requirements. - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Large aluminium reflector, inside finished in special white paint for max. light reflection - Aluminium cover, painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components are arranged on a block - Connection with adapter jack -Available in any RAL or DB colour without surcharge -Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711
Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	48%
Lamp flux	4000 lm	ULOR	11%
Luminous efficacy	21 lm/W	Total flux	1908 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 24.21 in
Diameter: 9.84 in

Electric

System power: 89 W

Protection

IP: 55