

Product data sheet

CONCIDO PENDANT LED D/I 57W LED 3000K CD WHITE
8246087009
SG ARMATUREN



Concido Pendant LED is designed for a variety of applications where an elegant and effective direct/indirect lighting solution is required. Concido Pendant LED is suitable for raised ceiling areas such as lobby and entrance halls, shopping malls and other retail environments. The decorative matt blasted opal glass provides a comfortable indirect light. Facility to independently switch direct and indirect light sources. Light distribution Direct/Indirect. Light source LED (3000K): 57W Ra > 80 SDCM: 3 L70/B50 >50.000h at Ta=25°C. Optics Direct: Plain mirror reflector. Materials and finish Housing: Aluminium, powder coated textured sparkle grey or white RAL9010 25% gloss. Reflector in aluminium. Bezel: Die-cast aluminium, powder coated textured sparkle grey or white RAL9010 25% gloss. Opal glass matt blasted. Control Gear On/off DALI Protection Class I, IP20, Ta=25°C, CE. Mounting/Connection Wire suspended. Pre-wired with 5.0m wire and cable. Suspension bracket and cover for ceiling mounting is included. How to specify: Suspended mounted direct/indirect, teardrop profile luminaire, finished in white or texture sparkle grey, complete with matt blasted opal glass, direct component provided by LED. Including 5 metre wire suspension and cable. Supplied with 5 metre wire and cable, suspension bracket and cover for ceiling mounting. As Riegens Concido Pendant LED range.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	57 W	CRI	80
Total flux	5260 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	26%
		Total power	57 W

Mounting mode

Pendant

Shape and measurements

Length: 11.50 in

Width: 11.50 in

Height: 24.61 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 57 W

Appliance Class: I

Protection

IP: 20