Product data sheet

PAULA V (BEADED) 9.645.3042.06

LEIPZIGER LEUCHTEN








Recommended mounting height 4.50 - 6.00 m, other heigts please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order special pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| 1 x High pressure mercury vapour lamp | |
|---------------------------------------|---------|
| Nominal lamp power | 80 W |
| Lamp flux | 4000 lm |
| Luminous efficacy | 39 lm/W |
| CCT | 3400 K |
| CRI | 54 |

| 86% |
|---------|
| 3449 lm |
| 89 W |
| |

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in Diameter: 28.74 in Electric

System power: 89 W

Protection

IP: 55