Product data sheet


LUCAS VIII (WALL FITTING BEADED) 9.828.3066.16 LEIPZIGER LEUCHTEN

High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz

IP 55

Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| A | |
|---|--|

| 1 x High pressure mercury vapour lamp | | | | | |
|---------------------------------------|---------|-------------|---------|--|--|
| Nominal lamp power | 125 W | LOR | 80% | | |
| Lamp flux | 6800 lm | ULOR | 4% | | |
| Luminous efficacy | 40 lm/W | Total flux | 5439 lm | | |
| CCT | 3400 K | Total power | 137 W | | |
| CRI | 54 | | | | |
| | | | | | |

| 1 x High pressure mercury | v vapour lamp | | |
|---------------------------|---------------|-------------|---------|
| Nominal lamp power | 80 W | LOR | 80% |
| Lamp flux | 4000 lm | ULOR | 4% |
| Luminous efficacy | 36 lm/W | Total flux | 3199 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |

Mounting mode Wall mounted Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Electric

System power: 89-137 W

Protection

IP: 55