


# Product data sheet

DKN QUADRAT  
10442.002  
RZB




IP  
40

IK  
02

Series: DKN-Quadrat, seidenglanz Type of Protection: IP 40 Protection Class: I Voltage: ~ 250 / 0 - 60 Hz Base: metal, galvanised. Diffuser fastening: tilt springs (DKN system: push/tilt system). Diffuser: hand-blown opal glass, silk finish. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 360, B 360, H 110 Lamp: 2 x E27 max. 75 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Beam Angle: 69°/62°/68°/67° Unified Glare Ratio: 17,8 EEC: A++ - E

## Light output 1



### 2 x Compact fluorescent lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 21 W    | Socket      | E27     |
| Lamp flux          | 1260 lm | LOR         | 63%     |
| Luminous efficacy  | 38 lm/W | ULOR        | 15%     |
| CCT                | 2700 K  | Total flux  | 1590 lm |
| CRI                | 80      | Total power | 42 W    |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 14.17 in  
Width: 14.17 in  
Height: 4.33 in

## Adjustability

Fixed

## Electric

System power: 42 W

## Protection

IP: 40  
IK: 02