

Product data sheet

FLAT POLYMERO KREIS
311953.002.1.76
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 98 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: AC power, DALI dimmable Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1950lm System power: 21W Beam Angle: 120° Number of fittings B10A: 87 Number of fittings B16A: 139 Number of fittings C10A: 87 Number of fittings C16A: 139 Inrush current: 0,1A Unified Glare Ratio: 18,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	21 W	CRI	80
Total flux	1950 lm	LOR	100%
Luminous efficacy	93 lm/W	ULOR	10%
		Total power	21 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.86 in
Diameter: 20.28 in

Adjustability

Fixed

Electric

System power: 21 W

Protection

IP: 40
IK: 03