Product data sheet

PRELUDE WHITE W/ OUTLET 1000LM 2700K RA>90 111341

SG ARMATUREN










Design: Hallvard Jakobsen Mirror luminaire with and without an outlet behind a lift-up lid. Luminaire made of metal and aluminium, and diffuser made of polycarbonate. Mounting as both concealed and visible installation, with flexible access to cables, and mounting in clips with option of additional wiring. Light distribution Direct Light technic LED 16W 2700K Ra>90 SDCM 3 L70/B10 >50,000 hrs Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Acrylic Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 23, B16: 37, C10: 29, C16: 46

Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT
16 W	CRI
1000 lm	LOR
62 lm/W	ULOR
	Total power

CCT	2700 K
CRI	90
LOR	100%
ULOR	24%
Total power	16 W

Mounting mode

Wall mounted

Shape and measurements

Length: 22.05 in Width: 3.15 in Height: 2.76 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 16 W Appliance Class: I

Protection

IP: 20 IK: 05