


# Product data sheet

CARLO V (CLEAR ATTACHMENT)  
9.896.5547.106  
LEIPZIGER LEUCHTEN



Suitable for mounting heights from 3 metres to 4 metres, for medium lighting requirements. - Excellent uniformity of light distribution while protection against glare - Base made of corrosion-resistant cast aluminium - Cap made of aluminium - Luminaire glazing made of UV-stabilised impact resistant clear polycarbonate. - Extra glazing above the reflector - Special mirror disc reflector system made of highest grade aluminium, polished and anodised in order to direct the light and to protect against glare. - Including head mirror but without reflector - Easy lamp change - One gear tray includes all electrical components - Simple connection with adapter jack - Luminaire available in any RAL or DB colour as required - Special pole  $\varnothing$  76 mm with 3 threads M8 (AZ...76/3M8), please order separately (full range of poles see page 362)

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	42 W	LOR	52%
Lamp flux	3200 lm	ULOR	17%
Luminous efficacy	36 lm/W	Total flux	1657 lm
CCT	2899 K	Total power	46 W
CRI	90		

## Mounting mode

Pole top mounted

## Electric

System power: 46 W

## Shape and measurements

Height: 19.69 in  
Diameter: 6.89 in