


# Product data sheet

LADOR 4 FLOODLIGHTS,PROJECTORS  
LD-50031-W-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° C 135,000 - Life time L80B10 Ta 50° C 310,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request for LD-50021, LD-50031 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	39.3 W	CRI	80
Total flux	3258 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	39.3 W

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Length: 4.72 in  
Width: 5.71 in  
Height: 7.68 in  
Weight: 3 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 39.3 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Surface temperature: 40°C