Product data sheet

SMART LOTIS 82 IP55 LED GE 3000K MEDIUM GOLD 12442346

MODULAR









Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask to form the perfect solution for any interior. Smart Lotis comes with the typical Lotis cup. Choose from a white or black structure.

Light output 1




| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 13.4 W |
| Lamp flux | 994 lm |
| Luminous efficacy | 63 lm/W |
| CCT | 3000 K |
| CRI | 90 |
| | |

| LOR | 85% |
|-------------|--------|
| Total flux | 844 lm |
| Total power | 13.4 W |
| | |



| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 6.2 W |
| Lamp flux | 576 lm |
| Luminous efficacy | 79 lm/W |
| CCT | 3000 K |
| CRI | 90 |
| | |

| LOR | 85% |
|-------------|--------|
| Total flux | 489 lm |
| Total power | 6.2 W |
| | |



| 1 x LED | | |
|--------------------|---------|-------------|
| Nominal lamp power | 9.2 W | LOR |
| Lamp flux | 773 lm | Total flux |
| Luminous efficacy | 71 lm/W | Total power |
| CCT | 3000 K | |
| CRI | 90 | |

Mounting mode

Ceiling recessed

Electric

System power: 6.2-13.4 W Appliance Class: II 85% 656 lm 9.2 W

Shape and measurements

Height: 0.39 in Diameter: 3.23 in

Adjustability

Fixed

Protection

IP: 55