


Product data sheet

PURE 3 DOWNLIGHT
09.1805/CDM-R111/35W/10°24°40°
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.

Light output 1




1 x Metal halide lamp

Nominal lamp power	35 W	Socket	Gx8.5
Lamp flux	3200 lm	LOR	51%
Luminous efficacy	42 lm/W	Total flux	1619 lm
CCT	3000 K	Total power	39 W
CRI	80		



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	Gx8.5
Lamp flux	3200 lm	LOR	51%
Luminous efficacy	42 lm/W	Total flux	1630 lm
CCT	3000 K	Total power	39 W
CRI	80		



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	Gx8.5
Lamp flux	3200 lm	LOR	42%
Luminous efficacy	34 lm/W	Total flux	1343 lm
CCT	3000 K	Total power	39 W
CRI	80		

Mounting mode

Ceiling recessed

Electric

System power: 39 W
Appliance Class: I

Shape and measurements

Length: 5.91 in

Width: 5.91 in

Height: 5.51 in

Adjustability

Rotatable, Tilttable

Protection

IP: 20