


# Product data sheet

LERS4B/LESQS4B LED 4" SHALLOW ROUND AND SQUARE CYLINDERS  
 LD4B20DE010W2N2765 EU4B1020W2N902765 4LBSQ0LI  
 COOPER LIGHTING



Mounting: ceiling, wall, stem, aircraft cable; Down or up/down styles, Shallow extruded housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-3000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	100
Total flux	1468 lm	LOR	100%
Luminous efficacy	52 lm/W	Total power	28 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 4.50 in  
 Width: 4.50 in  
 Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 28 W

## Protection

IP: 47