
Product data sheet

PLANIA TWIN 631162.004

RZB






L



Series: Plania Type of Protection: IP 65 Protection Class: I Voltage: 230 - 240 V / 50 - 60 Hz Base and housing: aluminium extrusion profiles, powder-coated. Reflector: aluminium, white coated. End caps: plastic. Front cover: aluminium extrusion profile, powder-coated. Front panel: PMMA, satin finish, double sided. Double sided light emission. LED included. Available Colours: silver, metallic Type of Installation: Wall (surface) Dimensions: L 250, B 92, H 380 Lamp: LED Colour Temperature: 6500K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 280lm System power: 8W Beam Angle: 0°/17°/24°/24° Number of fittings B10A: 17 Number of fittings B16A: 27 Number of fittings C10A: 28 Number of fittings C16A: 46 Inrush current: 27A EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	8 W	CRI	80
Total flux	280 lm	LOR	100%
Luminous efficacy	35 lm/W	ULOR	49%
		Total power	8 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.62 in Width: 9.84 in Height: 14.96 in

Adjustability

Fixed

Electric

System power: 8 W

Protection

IP: 65 IK: 03