
Product data sheet


FL2093/8 CARILLON FRANKLITE



Carillon 600mm Square 8lt Flush Smooth glass rods suspended from a chrome finish ceiling plate. Suitable for dimming if used with mains voltage halogen lamps. LED G9 lamps may be used but suitability for dimming will depend on the lamp and switch used.


IP 20

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	55%
		Total power	3 W

Ceiling mounted

Shape and measurements

Length: 19.69 in Width: 19.69 in Height: 12.61 in

Adjustability

Fixed

Electric System power: 24 W

Protection

IP: 20