

Product data sheet

GOLAS MINI

911437.004

RZB




IP
20

IK
03

Series: Golas Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Passive cooling. Rotates 356° horizontally and swivels 65° vertically. Installation without tools thanks to spring fastening system. Heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools. LED included. Connected converter included in separate gearbox. Available Colours: silver Type of Installation: Recessed ceiling mounting Dimensions: D 143, H 3 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2350lm System power: 19W Beam Angle: 62° Number of fittings B10A: 21 Number of fittings B16A: 34 Number of fittings C10A: 35 Number of fittings C16A: 57 Inrush current: 18,6A Unified Glare Ratio: 20,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	1850 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	20 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.12 in

Diameter: 5.63 in

Adjustability

Rotatable, Tilttable

Electric

System power: 20 W

Protection

IP: 20

IK: 03