Product data sheet


DEFINE LED SUSPENDED LUMINAIRE S122DIP-S865D925U927-4F0-1E-UDD-D4 COOPER LIGHTING



Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

IP 47

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	60.5 W	CRI	90
Total flux	5632 lm	LOR	100%
Luminous efficacy	93 lm/W	ULOR	56%
		Total power	60.5 W

Mounting mode	Electric
Pendant	System power: 60.5 W
Shape and measurements	Protection
Length: 48.00 in	IP: 47
Width: 2.00 in	
Height: 1.00 in	

Created by luminaires.dialux.com (3 May, 2024)

Adjustability

Fixed