Product data sheet

NORA VII (1-ARMED) 9.777.3062.05

LEIPZIGER LEUCHTEN








For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury vapour lamp | |
|---------------------------------------|---------|
| Nominal lamp power | 125 W |
| Lamp flux | 6800 lm |
| Luminous efficacy | 38 lm/W |
| CCT | 3400 K |
| CRI | 54 |
| | |

| LOR | 76% |
|-------------|---------|
| ULOR | 2% |
| Total flux | 5182 lm |
| Total power | 137 W |
| | |

Mounting mode

Pole top mounted

Shape and measurements

Height: 11.81 in Diameter: 21.26 in Electric

System power: 137 W

Protection

IP: 55