


Product data sheet

ANESTI POST TOP LUMINAIRES
AN-20595-W40
LIGMAN



· Lamp COB · CRI Ra > 80 · Mac Adam 3 SDCM · Life time L90B10 Ta 25° C 50,700 · Life time L80B10 Ta 50° C > 65,300 · Colour temperature : 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear, acrylic PMMA diffuser

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	41.2 W	CRI	80
Total flux	1005 lm	LOR	100%
Luminous efficacy	24 lm/W	ULOR	19%
		Total power	41.2 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 137.20 in
Diameter: 29.21 in
Weight: 26.9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 41.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 55
IK: 07
Surface temperature: 40°C