Product data sheet


LUCAS VIII (WALL FITTING) 9.828.3046.15 LEIPZIGER LEUCHTEN



High-quality mirror optics provide good glare protection and enable mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

IP 55

Light output 1



1 x High pressure mercury vapour lamp					
Nominal lamp power	50 W	LOR			
Lamp flux	2000 lm	ULOR			
Luminous efficacy	27 lm/W	Total flux			
CCT	3400 K	Total power			

54

$++\times$	YAT
	\mathcal{H}
	-KK
XI	TY.
\sim	

1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	80%		
Lamp flux	4000 lm	ULOR	4%		
Luminous efficacy	36 lm/W	Total flux	3186 lm		
CCT	3400 K	Total power	89 W		
CRI	54				

Mounting mode Electric Wall mounted System power: 59-89 W Shape and measurements Protection Height: 22.44 in IP: 55

1

CRI

Created by luminaires.dialux.com (19 May, 2024)

Diameter: 22.44 in

80%

4%

1593 lm

59 W