


Product data sheet

FLAT POLYMER0
311918.002.2.76
RZB



Series: FLAT POLYMER0 Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 35 mm. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. Colour: white Diameter: 360 mm Height: 100 mm Suspension length: 200-1300 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 14 W Rated luminous flux: 1500 lm Luminous efficiency: 107 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14 W	CRI	80
Total flux	1500 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	8%
		Total power	14 W

Mounting mode

Pendant

Shape and measurements

Height: 3.94 in

Diameter: 14.17 in

Adjustability

Fixed

Design

Material impression: Matt

Electric

System power: 14 W

Ballast: ECG

Controller: DALI

Protection

IP: 40

IK: 10

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F