Product data sheet

ZEAT 1 FLOODLIGHTS, PROJECTORS ZE-50019-M-W40

LIGMAN










- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One cable gland supplied with 1 m of 2x1.5 sqmm outdoor cable for ZE-50029, ZE-50030 - Through wiring on request for ZE-50391, ZE-50392 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Include control gear for ZE-50391, ZE-50392 - Remote driver is included for ZE-50019, ZE-50020, ZE-50029, ZE-50030

Light output 1 (integrated)



| Lamp type | LED | CCT | 4032 K |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 14.3 W | CRI | 80 |
| Total flux | 1070 lm | LOR | 100% |
| Luminous efficacy | 75 lm/W | Total power | 14.3 W |

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 3.23 in Diameter: 4.02 in Weight: 1 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 14.3 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65 IK: 07

Surface temperature: 40°C